Installation and Owner Care Guide

D-Day (Day of Dock) - Installation Preparation

To ensure a smooth and efficient installation of your AfriDock system, please complete the following steps before our team's arrival:

• Remove all equipment from the installation area.

Example: boats, jet skis, or any other watercraft or floating equipment.

- Access to the waterfront (Preferably for a bakkie and trailer), launchpad or slipway. (Assembly of the AfriDock on arrival +- 2 hours depending on size)
- Electric or power outlet (If needed)
- Dismantle and remove any old floating jetties or walkways that are not part of the new installation.
- Clear the area of any debris, aquatic plants, or obstructions that may hinder installation or AfriDock stability.



Care & Maintenance Manual

To maintain the performance, safety, and longevity of your AfriDock system, we recommend these simple care guidelines:

Before Use

- Ensure all AfriDock fasteners are securely tightened. (2-clicks)
- Confirm that all blocks are fitted with the correct AfriDock bolts and nuts.



 Only use biodegradable, aquatic safe and environmentally safe cleaning products around or on AfriDock.

Cleaning & Maintenance

- Rinse the AfriDock regularly with a garden hose or pressure washer to remove dirt, algae, and contaminants.
- Do not use corrosive chemicals, abrasive polishes, or harsh cleaning agents.



• Clean surrounding water and shoreline regularly to prevent the buildup of vegetation or waste around the AfriDock.

Repairs & Replacements

- Conduct visual inspections regularly. Look out for:
- Broken or missing lugs, pins, or other components
- Cracks, dents, or visible wear on AfriDock blocks

▲ Promptly replace any damaged or missing parts to maintain safety and buoyancy. ▲

- Do not exceed the AfriDock's maximum load capacity.
- Overloading the AfriDock may lead to damage or potential injury.
- Ensure all equipment left overnight is securely fastened or anchored to the AfriDock.
- When parking and tying the boat next to the AfriDock, using a bungee cord prevents strain on the cleat or block ear.

Weather & Flood Safety

- Stay informed about local flood or severe weather warnings in flood-prone areas.
- Keep away from any dock or floating device during flooding or severe weather.

⚠ In case of flood risk or storms, secure the dock firmly or temporarily remove it to prevent damage or loss. ⚠

Longevity Tips

- Schedule routine cleaning and inspections.
- Tighten hardware as needed.
- Avoid dragging heavy or sharp objects across the surface.
- With the proper care, your AfriDock system will provide years of safe and reliable use.

Contact us:

Mobile: 082 574 3116 (Andrew)

Mobile: 083 280 4690 (Roelof)

E-mail: admin@afridock.com

Web Address: www.afridock.com

